

3 Poles Thermal-Magnetic Adjustable Type MCCB (For Motor Protection)



	Type Code	Rated Current In (A)	Thermal Adj. Current Ir(A)	Instantaneous Tripping Current (Im)	Breaking Capacity Icu (kA)	Pcs in a Box	Order Code
Thermal Adjustable - Magnetic Fixed	K160	25	18-25	15xIn	36	8	MK160025
		32	23-32	15xIn	36	8	MK160032
		40	28-40	15xIn	36	8	MK160040
		50	35-50	15xIn	36	8	MK160050
		63	44-63	15xIn	36	8	MK160063
		80	56-80	15xIn	36	8	MK160080
		100	70-100	15xIn	36	8	MK160100
		125	88-125	15xIn	36	8	MK160125
Thermal Adjustable - Magnetic Adjustable	K250	200	140-200	(10-15)xIn	36	6	MK250200
		250	175-250	(10-15)xIn	36	6	MK250250
	K400 (with Extension Bar)	315	250-315	(8-12)xIn	36	2	MK400315
		400	315-400	(8-12)xIn	36	2	MK400400
	K630 (with Extension Bar)	500	400-500	(8-12)xIn	36	2	MK630500
		630	500-630	(8-12)xIn	36	2	MK630630

3 Poles Thermal-Magnetic Adjustable Type MCCB (Protection for Power Distribution & Network)



	Type Code	Rated Current In (A)	Thermal Adj. Current Range Ir (A)	Instantaneous Tripping Current (Im)	Breaking Capacity Icu (kA)	Pcs in a Box	Order Code
Thermal Adjustable - Magnetic Fixed	B160	25	20-25	10xIn	25	8	3B160025
		32	25-32	10xIn	25	8	3B160032
		40	32-40	10xIn	25	8	3B160040
		50	40-50	10xIn	25	8	3B160050
		63	50-63	10xIn	25	8	3B160063
		80	63-80	10xIn	25	8	3B160080
		100	80-100	10xIn	25	8	3B160100
		125	100-125	10xIn	25	8	3B160125
	B250	200	160-200	10xIn	36	4	3B250200
		250	200-250	10xIn	36	4	3B250250
	K160	25	18-25	10xIn	36	6	3K160025
		32	23-32	10xIn	36	6	3K160032
		40	28-40	10xIn	36	6	3K160040
		50	35-50	10xIn	36	6	3K160050
		63	44-63	10xIn	36	6	3K160063
		80	56-80	10xIn	36	6	3K160080
		100	70-100	10xIn	36	6	3K160100
		125	88-125	10xIn	36	6	3K160125
Thermal Adjustable - Magnetic Adjustable	K250	63	44-63	(5-10)xIn	36	6	3K250063
		80	56-80	(5-10)xIn	36	6	3K250080
		100	70-100	(5-10)xIn	36	6	3K250100
		125	88-125	(5-10)xIn	36	6	3K250125
		160	112-160	(5-10)xIn	36	6	3K250160
		200	140-200	(5-10)xIn	36	6	3K250200
		250	175-250	(5-10)xIn	36	6	3K250250
	K400	315	250-315	(5-10)xIn	36	2	3K400315
		400	315-400	(5-10)xIn	36	2	3K400400
	K630	500	400-500	(5-10)xIn	36	2	3K630500
		630	500-630	(5-10)xIn	36	2	3K630630